

Design of Information Systems

UML Modeling Concepts and Introduction to USE

Martin Gogolla
University of Bremen, Germany
Database Systems Group

Goals of object-oriented modeling

- Integrated description of structure and behavior of objects
- Representation for properties of objects and relationships between objects
- Development of object descriptions capturing state transitions and object lifecycles
- Options to describe type level and instance level aspects
- Modeling language used here: Unified Modeling Language (UML)

Good reference book on UML (Unified Modeling Language)

James Rumbaugh, Ivar Jacobson, Grady Booch
Unified Modeling Language Reference Manual, Second Edition
ISBN 0321245628
Pearson Higher Education

Excerpts (tables, quotations, diagrams, ...) in the course slides

Table 3-1: UML Views and Diagrams

<i>Major Area</i>	<i>View</i>	<i>Diagram</i>	<i>Main Concepts</i>
structural	static view	class diagram	association, class, dependency, generalization, interface, realization
	design view	internal structure	connector, interface, part, port, provided interface, role, required interface
		collaboration diagram	connector, collaboration, collaboration use, role
		component diagram	component, dependency, port, provided interface, realization, required interface, subsystem
use case view	use case diagram	actor, association, extend, include, use case, use case generalization	

Table 3-1: UML Views and Diagrams (continued)

<i>Major Area</i>	<i>View</i>	<i>Diagram</i>	<i>Main Concepts</i>
dynamic	state machine view	state machine diagram	completion transition, do activity, effect, event, region, state, transition, trigger
	activity view	activity diagram	action, activity, control flow, control node, data flow, exception, expansion region, fork, join, object node, pin
	interaction view	sequence diagram	occurrence specification, execution specification, interaction, interaction fragment, interaction operand, lifeline, message, signal
		communication diagram	collaboration, guard condition, message, role, sequence number

Basic diagrams explained by example model for a social network





- Class diagram
- Use case diagram
- Object diagram
- State chart diagrams
- Sequence diagram and communication diagram (Interaction)
- Activity diagram
- Diagrams enriched and made precise by expressions written in OCL (Object Constraint Language) being part of UML
- OCL expression itself without side-effect: no system state change
- Operation definitions, class invariants, operation pre- and postconditions (operation contracts), ...
- Explained with UML-based Specification Environment (USE)

UML-based Specification Environment (USE)

- steps to install USE under Windows XY
- google: use ocl bremen
- -> <https://sourceforge.net/projects/useocl/>
- download zip file "use-X.Y.Z.zip"; save file on Desktop
- unzip file to Desktop directory use-X.Y.Z
- on Desktop context menu "new link" (e.g. "use-4.2.0"); let the link point to:
- use-X.Y.Z/bin/start_use.bat
- double click your link to start USE with an empty model
- USE offers CLI and GUI
- optional: adjust CLI via properties (font, colors, ...)

USE and OCL for the impatient: 9 OCL expressions on the CLI


- ?21+21
- ?20.9+21.1
- ?20.9+21.1=42
- ?'for'+ 'tytwo'
- ?Set{7,9,5}
- ?Bag{7,9,5,7}
- ?Bag{7,9,5,7}=Bag{5,7,9}
- ?Set{7,9,5,7}=Set{5,7,9}
- ?Set{7,9}->union(Set{9,5})->select(i|i<9)
- OCL: datatypes, collections, operations



Class diagram concepts (used in the example)

- USE diagrams customizable via context menu; layout storable
- Class, attribute, operation, parameter, (return) type
- OCL collection kind Set(T),
more collection kinds: Bag(T), Sequence(T), ...
superclass Collection(T) > Set(T), Collection(T) > Bag(T), ...
- Binary association, association class, reflexive association, composition, ..., generalization, aggregation
- composition, aggregation: part-whole relationships, acyclic on objects, composition strong binding (0..1), aggregation weak binding (0..*)
- Role, association name, multiplicities
- Roles used for navigation from one object to other objects

Example for class diagram concepts (generalization, multiplicities)



Operation and invariant definition with OCL

```
class Profile
```

```
operations
```

```
  friends() : Set(Profile) =
```

```
    friendship[inviter] ->select(oclInState(accepted)) .invitee ->union(
```

```
    friendship[invitee] ->select(oclInState(accepted)) .inviter) ->asSet()
```

```
  friendship(anInviter: Profile) : Friendship =
```

```
    self.friendship[invitee] ->any(fs | fs.inviter = anInviter)
```


```
constraints
```

```
  inv asymmetricFriendship: invitee ->intersection(inviter) ->isEmpty()
```

```
  inv uniqueUserName: Profile.allInstances ->isUnique(userName)
```


- class invariant with name and boolean OCL expression
- query operation definition; class-valued or collection-valued
- roles
- collection operations allInstances, intersection, isEmpty, isUnique, ...

Use case diagram and concepts




- Actor, use case ("specification of an action sequence"), attributes
- Use case relationships: include (mandatory, once), extend (optional, repeatable), generalization
- not supported in USE

Object diagram and concepts





- Object (class), link (association), attribute value (attribute)
- Instance level in object diagram, type level in class diagram

Object diagram




State chart diagram and concepts




- State, state invariant
- Initial, final, normal state
- State transition: [guard] event / [postcondition]
- determine object life cycles
- determined here: protocol state machines; operation call sequences

State chart diagram and concepts: guard




- State transition: [guard] event / [postcondition]
- guard, also called precondition:
[not aSpouse.oclInState(married)] marry(aSpouse)

Object diagram with roles, association names, state chart status





Sequence diagram



```
Command list
1. !new Profile('merkel')
2. !new Profile('putin')
3. !new Profile('trump')
4. !merkel.init('Angela', 'Merkel', 'muddi')
5. !putin.init('Vladimir', 'Putin', 'crab')
6. !trump.init('Donald', 'Trump', 'theDonald')
7. !putin.invite(merkel)
8. !trump.invite(putin)
9. !putin.decline(trump)
10. !merkel.accept(putin)
11. !p := merkel.publish('BMW, we have a problem')
12. !new Profile('may')
13. !may.init('Theresa', 'May', 'motherTheresa')
14. !putin.comment(p, 'May the Donald be with you')
15. !may.invite(merkel)
```


Sequence diagram



Sequence diagram concepts

- Object (or object role)
- Lifeline
- Activation
- Message representation:
 - solid arrow from caller to callee indicating message call
 - dashed arrow from callee to caller
 - indicating message completion, optional with return value
- Link representation: link shown as link object with lifeline

Communication diagram and concepts




- Object, message, message number, link representation

Sequence vs Communication diagram

Both sequence diagrams and communication diagrams show interactions, but they emphasize different aspects. A sequence diagram shows time sequence as a geometric dimension, but the relationships among roles are implicit. A communication diagram shows the relationships among roles geometrically and relates messages to the connectors, but time sequences are less clear because they are implied by the sequence numbers. Each diagram should be used when its main aspect is the focus of attention.

UML Reference Manual, p. 40

Activity diagram and concepts



- Initial, final, decision, action node; not supported in USE

Textual model definition in USE (part A)

```
class Profile
attributes
  firstN:String init: ''
  ...
  initials:String derived:
    firstN.substring(1,1).concat(lastN.substring(1,1))
operations
  init(aFirstN:String, aLastN:String, aUserN:String)
  begin
    self.firstN:=aFirstN; self.lastN:=aLastN; self.userN:=aUserN
  end
  pre  aUserNNonEmpty: aUserN<>' '
  post userNAssigned:  aUserN=userN
  ...
constraints
  inv uniqueUserName: Profile.allInstances->isUnique (userN)
  ...
statemachines
  psm ProfileLife
  states
    born      [userN=' ' ]
    ...
  transitions
    born      -> living { init() }
    ...
  end
end
```

Textual model definition in USE (part B)

```
associationclass Friendship between
  Profile [*] role inviter
  Profile [*] role invitee
attributes
  status:String init:'pending'
...
end
```

```
composition PosterPosting between
  Profile [1] role poster
  Posting [*] role posting
end
```

```
associationclass Commenting between
  Profile [*] role commenter
  Posting [*] role commented
attributes
  comment:String
...
end
```

```
association Interest between
  Profile [*]
  Subject [*]
end
```

Textual model definition in USE (complete model part A)

```
model SocialNetwork
```

```
class Profile
```

```
attributes
```

```
  firstN:String init: ''
```

```
  lastN:String init: ''
```

```
  userN:String init: ''
```

```
  initials:String derived:
```

```
    firstN.substring(1,1).concat(lastN.substring(1,1))
```

```
operations
```

```
  init(aFirstN:String, aLastN:String, aUserN:String)
```

```
    begin
```

```
      self.firstN:=aFirstN; self.lastN:=aLastN; self.userN:=aUserN end
```

```
    pre  aUserNNonEmpty: aUserN<>''
```

```
    post userNAssigned: aUserN=userN
```

```
  invite(anInvitee:Profile)
```

```
    begin new Friendship between (self,anInvitee) end
```

```
    pre  notAlreadyTried: invitee->union(inviter)->excludes(anInvitee)
```

```
    post madeFS: friendship[inviter]->
```

```
      select(oclInState(pending)).invitee->includes(anInvitee)
```

```
  accept(anInviter:Profile)
```

```
    begin self.friendship(anInviter).acceptF() end
```

```
    pre  pendingFS: friendship[invitee]->
```

```
      select(oclInState(pending)).inviter->includes(anInviter)
```

```
    post acceptedFS: friendship[invitee]->
```

```
      select(oclInState(accepted)).inviter->includes(anInviter)
```

Textual model definition in USE (complete model part B)

```
decline (anInviter:Profile)
  begin self.friendship(anInviter).declineF() end
  pre pendingFS: friendship[invitee]->
      select(oclInState(pending)).inviter->includes(anInviter)
  post declinedFS: friendship[invitee]->
      select(oclInState(declined)).inviter->includes(anInviter)
publish(aPostText:String):Posting
  begin declare p:Posting;
  p:=new Posting(); p.posting:=aPostText;
  insert(self,p) into PosterPosting; result:=p
  end
  pre nonEmpty: aPostText<>' '
  post newPosting: Posting.allInstances->exists(p |
      p.posting=aPostText and result=p)
comment(aPosting:Posting,aComment:String)
  begin declare c:Commenting;
  c:=new Commenting between (self,aPosting); c.comment:=aComment
  end
  pre aPostingNonNullACommentNonEmpty: aPosting<>null and aComment<>' '
  post commentingExists: Commenting.allInstances->exists(c |
      c.comment=aComment and aPosting.commenting->includes(c) and
      self.commenting->includes(c))
```

Textual model definition in USE (complete model part C)

```
friends() : Set(Profile) =  
    friendship[inviter] -> select(oclInState(accepted)) . invitee -> union(  
        friendship[invitee] -> select(oclInState(accepted)) . inviter) -> asSet()  
friendship(anInviter: Profile) : Friendship =  
    self.friendship[invitee] -> any(fs | fs.inviter = anInviter)
```

constraints

```
inv asymmetricFriendship: invitee -> intersection(inviter) -> isEmpty()  
inv uniqueUserName: Profile.allInstances -> isUnique(userN)
```

statemachines

psm ProfileLife

states

prenatal: initial

born [userN = '']

living [userN <> '']

transitions

prenatal -> born { create }

born -> living { init() }

living -> living { invite() }

living -> living { accept() }

living -> living { decline() }

living -> living { publish() }

living -> living { comment() }

end

end

Textual model definition in USE (complete model part D)

```
associationclass Friendship between
  Profile [*] role inviter
  Profile [*] role invitee
attributes
  status:String init:'pending'
operations
  acceptF()
    begin self.status:='accepted' end
  declineF()
    begin self.status:='declined' end
statemachines
  psm FriendshipLife
  states
    prenatal:initial
    pending
    accepted:final
    declined:final
  transitions
    prenatal -> pending { create }
    pending -> accepted { acceptF() }
    pending -> declined { declineF() }
  end
end
```

Textual model definition in USE (complete model part E)

```
composition PosterPosting between
  Profile [1] role poster
  Posting [*] role posting
end
```

```
class Posting
attributes
  posting:String
end
```

```
associationclass Commenting between
  Profile [*] role commenter
  Posting [*] role commented
attributes
  comment:String
end
```

```
constraints
```

```
context Commenting inv commentOnlyByFriends:
  commented.poster.friends()->includes(commenter)
```

Textual model definition in USE (complete model part F)

```
class Subject
attributes
  subject:String
constraints
  inv noDuplicates:
    Subject.allInstances->size=Subject.allInstances.subject->asSet->size
end


association Interest between
  Profile [*]
  Subject [*]
end
```


Scenario definition on the USE shell with SOIL statements


```
!create merkel,putin,trump:Profile
!merkel.init('Angela','Merkel','muddi')
!putin.init('Vladimir','Putin','crab')
!trump.init('Donald','Trump','theDonald')
!putin.invite(merkel)
!trump.invite(putin)
!putin.decline(trump)
!merkel.accept(putin)
!p:=merkel.publish('BMW, we have a problem')
!create may:Profile
!may.init('Theresa','May','motherTheresa')
!putin.comment(p,'May the Donald be with you')
!may.invite(merkel)
```

- SOIL: Simple Ocl-like Imperative Language
- Object creation and destruction; link creation and destruction:
'create' / 'new', 'destroy', 'insert', 'delete'
- Variable declaration 'declare'; assignment ':=' with OCL expressions
- Loop/If: 'for' var 'in' collection 'do' ... 'end'; 'if' ... 'then' ... ['else' ...] end
- (Recursive) calls object.operation(parameter)
- SOIL statements on USE shell starting with '!'

Object diagram




Sequence diagram









Command list


1. !new Profile('merkel')
2. !new Profile('putin')
3. !new Profile('trump')
4. !merkel.init('Angela', 'Merkel', 'muddi')
5. !putin.init('Vladimir', 'Putin', 'crab')
6. !trump.init('Donald', 'Trump', 'theDonald')
7. !putin.invite(merkel)
8. !trump.invite(putin)
9. !putin.decline(trump)
10. !merkel.accept(putin)
11. !p := merkel.publish('BMW, we have a problem')
12. !new Profile('may')
13. !may.init('Theresa', 'May', 'motherTheresa')
14. !putin.comment(p, 'May the Donald be with you')
15. !may.invite(merkel)

Communication diagram





Evaluation of OCL expressions (Part A)



-- **allInstances** -----

?Profile.allInstances

Set{may,merkel,putin,trump}:Set(Profile)

-- **includes, excludes** -----

?Set{may,merkel,trump}->includes(putin)

false

?Set{putin}->excludes(trump)

true

Evaluation of OCL expressions (Part B)

-- **select, reject** -----

```
?Profile.allInstances->select(p | p.subject->includes(opera))  
Set{may,merkel}:Set(Profile)
```

```
?Profile.allInstances->reject(p | p.subject->includes(hairstyle))  
Set{putin}:Set(Profile)
```

-- **size, isEmpty, notEmpty** -----

```
?Profile.allInstances->select(p | p.subject->size=3)  
Set{may,merkel}:Set(Profile)
```

```
?Subject.allInstances->select(s | s.profile->size=0)  
Set{ocl}:Set(Subject)
```

```
?Subject.allInstances->select(s | s.profile->isEmpty)  
Set{ocl}:Set(Subject)
```

```
?Subject.allInstances->select(s | s.profile->notEmpty)  
Set{hairstyle,horses,opera,shoes}:Set(Subject)
```

Evaluation of OCL expressions (Part C)

```
-- forall, exists -----  
  
?Subject.allInstances->forall(s | s.profile->notEmpty)  
false:Boolean  
  
?Profile.allInstances->select(p | Subject.allInstances->exists(s1,s2 |  
    s1<>s2 and s1.profile->includes(p) and s2.profile->includes(p))  
Set{may,merkel}:Set(Profile)  
  
?Profile.allInstances->select(p | Subject.allInstances->exists(s1,s2 |  
    s1<>s2 and p.subject->includes(s1) and p.subject->includes(s2))  
Set{may,merkel}:Set(Profile)  
  
-- collectNested, collect, asSet -----  
  
?Profile.allInstances->collectNested(p | p.subject)  
Bag{Set{hairstyle},  
    Set{horses},                               ?Set{-2,0,2}->collect(i | i*i)  
    Set{hairstyle,opera,shoes},                 Bag{0,4,4}  
    Set{hairstyle,opera,shoes}}:Bag(Set(Subject))  
  
?Profile.allInstances->collect(p | p.subject)  
Bag{hairstyle,hairstyle,hairstyle,horses,opera,opera,shoes,shoes}:  
    Bag(Subject)  
  
?Profile.allInstances->collect(p | p.subject)->asSet      -- SQL distinct  
Set{hairstyle,horses,opera,shoes} : Set(Subject)
```


Evaluation of OCL expressions (Part D)

-- including, excluding -----

```
?Set{putin,merkel}->including(may)
Set{may,merkel,putin}: Set(Profile)
```

```
?Set{putin,merkel}->excluding(putin)
Set{merkel}: Set(Profile)
```

```
?Set{putin,merkel}->excluding(may)
Set{merkel,putin}: Set(Profile)
```

```
?Bag{opera,shoes,opera}->including(shoes)
Bag{opera,opera,shoes,shoes}: Bag(Subject)
```

```
?Bag{opera,shoes,opera}->excluding(opera) -- excluding radical on Bag(T)
Bag{shoes}: Bag(Subject)
```

-- (includesAll, excludesAll) = ('supersetOf', 'disjointFrom') -----

```
?Set{opera,shoes,hairstyle}->includesAll(Set{opera,hairstyle}) = true
```

```
?Set{opera,shoes,hairstyle}->includesAll(Set{opera,horses}) = false
```

```
?Set{opera,shoes}->excludesAll(Set{horses,hairstyle}) = true
```








```
?Set{opera,shoes}->excludesAll(Set{horses,opera}) = false
```

Evaluation of OCL expressions (Part E)

```
-- let, Tuple, product -----  
  
-- Profile objects having interest in a given set of subjects  
?let INTEREST=Set{hairstyle,opera} in Profile.allInstances->select(p |  
    INTEREST->forall(s | p.subject->includes(s)))  
Set{may,merkel}:Set(Profile)  
  
-- Profile objects with a maximum number of interests  
?let MAX=Profile.allInstances->collect(p | p.subject->size)->max() in  
    Profile.allInstances->select(p | p.subject->size=MAX)  
Set{may,merkel}:Set(Profile)  
  
-- Profile object pairs with the same set of interests  
?Profile.allInstances->product(Profile.allInstances)  
Set{Tuple{first=may,second=may},  
    Tuple{first=may,second=merkel},  
    ...  
    Tuple{first=trump,second=trump}} :  
    Set(Tuple(first:Profile,second:Profile)) -- 16 tuples  
  
?Profile.allInstances->product(Profile.allInstances)->  
    select(t | t.first.subject=t.second.subject and t.first<>t.second)  
Set{Tuple{first=may,second=merkel},Tuple{first=merkel,second=may}} :  
    Set(Tuple(first:Profile,second:Profile))
```

Evaluation of OCL expressions (Part F)

-- navigation in plain association class -----





Evaluation of OCL expressions (Part G)


-- navigation in reflexive association class -----

```
Profile::inviter : Set(Profile)
Profile::invitee : Set(Profile)
Profile::friendship[inviter] : Set(Friendship)
Profile::friendship[invitee] : Set(Friendship)
Friendship::inviter : Profile
Friendship::invitee : Profile
```

```
merkel.inviter = Set{may,putin}
merkel.invitee = Set{} : Set(Profile)
merkel.friendship[inviter] = Set{} : Set(Friendship)
merkel.friendship[invitee] = Set{Friendship1, Friendship3}
Friendship1.inviter = putin
Friendship1.invitee = merkel
```



Evaluation of OCL expressions (Part H)



Evaluation of OCL expressions (Part I)

-- dot shortcut -----

```
?merkel.inviter                               ?merkel.inviter->collect(p | p.userN)
Set{may,putin}: Set(Profile)                   Bag{'crab','motherTheresa'}: Bag(String)
```

```
?merkel.inviter.userN -- dot shortcut on single object
Bag{'crab','motherTheresa'}: Bag(String)
```

```
?Set{merkel}.inviter.userN -- dot shortcut on object collection
Bag{'crab','motherTheresa'}: Bag(String)
```

```
?Profile.allInstances.inviter.userN -- dot shortcut on object collection
Bag{'crab','motherTheresa','theDonald'}: Bag(String) -- excludes 'muddi'
```

```
?trump.invitee.invitee.inviter -- long path; object-valued result
Bag{may,putin}: Bag(Profile)
```

```
?trump.invitee.invitee.posting.posting -- long path; data-valued result
Bag{'BMW, we have a problem'}: Bag(String)
```

```
?Posting1.poster.initials -- respect multiplicities; gives single value
'AM' : String
```

```
?Posting1.poster.inviter -- respect multiplicities; gives Set(T)
Set{may,putin}: Set(Profile)
```

Derived attributes, query operations, invariants: Applying OCL

Derived attributes

```
Profile::initials:String derived:  
  firstN.substring(1,1).concat(lastN.substring(1,1))
```

Query operations

```
Profile::friends():Set(Profile)=  
  friendship[inviter]->select(oclInState(accepted)).invitee->union(  
    friendship[invitee]->select(oclInState(accepted)).inviter)->asSet  
Profile::friendship(anInviter:Profile):Friendship=  
  friendship[invitee]->any(fs|fs.inviter=anInviter)
```

Invariants

```
context Profile
```

```
  inv asymmetricFriendship: invitee->intersection(inviter)->isEmpty()  
  inv uniqueUserName: Profile.allInstances->isUnique(userN)
```


```
context Commenting inv commentOnlyByFriends:
```

```
  commented.poster.friends()->includes(commenter)
```

```
context Subject inv noDuplicates:
```

```
  Subject.allInstances->size=Subject.allInstances.subject->asSet->size
```

Object diagram with violated invariants



Thanks for your attention!